

CLAIM AMENDMENTS

1-12 (canceled)

13. (previously presented) A door closer including:

a door closer body formed with at least one channel for flow of a pressure medium controlling operation of the door closer and also formed with at least one bore that intersects the channel and has first and second segments at opposite respective sides of the channel, and

a control device fitted in the bore and having first and second opposite ends, the control device comprising a guiding part at its first end, the guiding part being located in the first segment of the bore and having a thread fillet engaging the door closer body and supporting the control device relative to the door closer body, a support part at the second end of the control device, the support part being located in the second segment of the bore, a collar of resilient material located in the second segment of the bore and surrounding the support part of the control device, the collar being under compression whereby the collar supports the second end of the control device relative to the door closer body and restrains the control device against rocking and swaying movement relative to the door closer body due to flow of pressure medium in said channel, and a control part between the guiding part and the support part and having a bevelled inner end for cooperating with the door closer body to restrict pressure medium flow in said channel,

whereby the control device can be moved in its axial direction by turning the control device supported on the door closer body for adjusting the restriction of the pressure medium flow by the control part.

14. (previously presented) A door closer according to claim 13, wherein the collar has at least one chase to reduce its thickness at a certain part of the collar.

15. (previously presented) A door closer according to claim 13, wherein the collar is plastic.

16. (new) A door closer according to claim 13, wherein the collar is plastic and has at least one chase to reduce its thickness at a certain part of the collar.

17. (new) A door closer according to claim 16, wherein said second segment of the bore is blind.

18. (new) A door closer including:

a door closer body formed with first and second channels for flow of a pressure medium controlling operation of the door closer and also formed with a first bore that intersects the first channel and has first and second segments at opposite respective sides of the first channel, and with a second bore that intersects the second channel and has first and second segments at opposite respective sides of the second channel,

a first control device fitted in the first bore and having first and second opposite ends, the first control device comprising a guiding part at its first end, the guiding part being located in the first segment of the first bore and having a thread fillet engaging the door closer body and supporting the first control device relative to the door closer body, a support part at the second end of the first control device, the support part being located in the second segment of the first bore, a collar of resilient material located in the second segment of the first bore and surrounding the support part of the first control device, the collar being under compression whereby the collar supports the second end of the first control device relative to the door closer body and restrains the first control device against rocking and swaying movement relative to the door closer body due to flow of pressure medium in said first channel, and a control part between the guiding part and the support part and having a bevelled inner

end for cooperating with the door closer body to restrict pressure medium flow in said first channel,

a second control device fitted in the second bore and having first and second opposite ends, the second control device comprising a guiding part at its first end, the guiding part being located in the first segment of the second bore and having a thread fillet engaging the door closer body and supporting the second control device relative to the door closer body, a support part at the second end of the second control device, the support part being located in the second segment of the second bore, and a control part between the guiding part and the support part and having a bevelled inner end for cooperating with the door closer body to restrict pressure medium flow in said second channel,

whereby the first control device can be moved in its axial direction by turning the first control device supported on the door closer body for adjusting the restriction of the pressure medium flow by the control part of the first control device and the second control device can be moved in its axial direction by turning the second control device supported on the door closer body for adjusting the restriction of the pressure medium flow by the control part of the second control device.

19. (new) A door closer according to claim 18, wherein the collar has at least one chase to reduce its thickness at a certain part of the collar.

20. (new) A door closer according to claim 18, wherein the collar is plastic.

21. (new) A door closer according to claim 18, wherein the collar is plastic and has at least one chase to reduce its thickness at a certain part of the collar.

22. (new) A door closer according to claim 21, wherein said second segment of the first bore is blind.

23. (new) A door closer according to claim 18, comprising a second collar of resilient material located in the second segment of the second bore and surrounding the support part of the second control device, the second collar being under compression whereby the second collar supports the second end of the second control device relative to the door closer body and restrains the second control device against rocking and swaying movement relative to the door closer body due to flow of pressure medium in said second channel.